

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 1

Revision: 17.03.2015

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: **RENOLIT ALKORPLUS – POLIQUID COMBI - PRIMER**

· Article number: 81802-001

· 1.2 Relevant identified uses of the substance or mixture and uses advised against See Section 16

· Application of the substance / the mixture Priming

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

RENOLIT Belgium NV
Industriepark De Bruwaan 43
B – 9700 OUDENAARDE
Tel: +32 55 33 97 11
Fax: +32 55 31 86 58
Internet: renolit.belgium@renolit.com / dirk.vandersype@renolit.com

· Emergency telephone number:

+44 (0)1235 239 670 (24 h / 7 days)

* SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 2

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 1)

· **Hazard-determining components of labelling:**

methyl methacrylate
Bisphenol-A-epichlorohydrin
2-ethylhexyl acrylate

· **Hazard statements**

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

· **Precautionary statements**

P261 A void breathing vapours.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking.

P280 W ear protective gloves/ eye protection.

P312 Call a POISON CENTER/ doctor if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

· **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

* SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|---|--|-----------|
| CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28 | methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 | 25-50% |
| CAS: 25068-38-6 NLP: 500-033-5 | Bisphenol-A-epichlorohydrin Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 | 25-50% |
| CAS: 103-11-7 EINECS: 203-080-7 Reg.nr.: 01-2119453158-37 | 2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412 | 2.5-<10% |
| | Hydrocarbons, C9-C12, n-alkanes, cyclic, aromatic (2-25%) Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336 | 0.1- 0.5% |

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

* SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.
Take affected persons out of danger area and lay down.
Involve doctor immediately.

· **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 3

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 2)

Seek medical treatment.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Disziness

Skin sensitization.

Irritant to skin, eyes and respiratory system.

· **4.3 Indication of any immediate medical attention and special treatment needed**

After inhalation, even in the absence of signs of disease, inhaled corticosteroid (eg Ventolair) give.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder, foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NO_x)

Vapours are heavier than air.

Crawling vapors can result in greater distance from the ignition!

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

· **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation



Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· **6.3 Methods and material for containment and cleaning up:**

Do not flush with water or aqueous cleansing agents

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 4

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 3)

6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

* SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Cool because of polymerization when heated container. By heat, keep containers with water. Cool Emergency cooling for the case of nearby fire. closed containers protect against heating (pressure rise). Avoid heat.
- Do not refill residue into storage receptacles.
- Ensure good ventilation/exhaustion at the workplace.
at least 7 air changes
- Prevent formation of aerosols.

Information about fire - and explosion protection:

- Highly volatile, flammable constituents are released during processing.
- Keep ignition sources away - Do not smoke.
- Fumes can combine with air to form an explosive mixture.
- Only explosion-proof equipment.
- Protect against electrostatic charges.
- Protect from heat.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

- Store only in the original receptacle.
- Store in a cool location.

Information about storage in one common storage facility:

- Store away from oxidising agents.
- Store away from foodstuffs.

Further information about storage conditions:

- Store in cool, dry conditions in well sealed receptacles.
- Storage in a collecting room is required.
- Store under lock and key and with access restricted to technical experts or their assistants only.
- max. Storage temperature 30 °C
- Keep container tightly sealed.
- Protect from heat and direct sunlight.

7.3 Specific end use(s) Building coating or sealing.

* SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate (25-50%)

| | |
|---------------------|--|
| WEL (Great Britain) | Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm |
| MAK (Switzerland) | Short-term value: 420 mg/m ³ , 100 ppm Long-term value: 210 mg/m ³ , 50 ppm S SSc; |

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 5

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 4)

| | | |
|---|---|--|
| 103-11-7 2-ethylhexyl acrylate (2.5-<10%) | | |
| MAK (Switzerland) | Short-term value: 38 mg/m ³ , 5 ppm Long-term value: 38 mg/m ³ , 5 ppm S SSc; | |
| · DNELs | | |
| 80-62-6 methyl methacrylate | | |
| Inhalative | DNE L (population) | 74.3 mg/m ³ (Long-term - systemic effects) 105 mg/m ³ (Long-term - local effects) |
| | DNEL (worker) | 210 mg/m ³ (Long-term - local effects) 210 mg/m ³ (Long-term - systemic effects) Long-term |
| 103-11-7 2-ethylhexyl acrylate | | |
| Dermal | DNEL | 242 µg/cm ² (Employee / Industrial / Commercial) Long-term and short-term |
| Inhalative | DNEL | 37.5 mg/m ³ (Employee / Industrial / Commercial) (Langzeit) |
| · PNECs | | |
| 80-62-6 methyl methacrylate | | |
| PNEC | < 0.94 mg/l (water) | |
| PNEC sediment | 1.47 mg/kg dw (ground) 5.74 mg/kg dw (freshwater) | |
| 103-11-7 2-ethylhexyl acrylate | | |
| Boden | 2.3 mg/l (Soil microorganisms) 1 mg/l (ground) | |
| PNEC | 0.0023 mg/kg (oral intake) | |
| water | 0.126 mg/l (sediment) 0.002727 mg/l (freshwater) | |

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Avoid contact with the eyes and skin.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Keep away from foodstuffs, beverages and feed.
- Do not inhale gases / fumes / aerosols.

· Respiratory protection:

- Ensure good ventilation.
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- The use of respiratory protective hood is recommended because not wearing time limitations apply.

· Protection of hands:

- Preventive skin protection by use of skin-protecting agents is recommended.



Protective gloves

After use of gloves apply skin-cleaning agents and skin cosmetics.
Check protective gloves prior to each use for their proper condition.

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 6

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Protective gloves according EN 374.

Suitable material: nitrile.

· **Penetration time of glove material**

Our Recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

Butyl rubber, BR

· **For the permanent contact gloves made of the following materials are suitable:** Butyl rubber, BR

· **Not suitable are gloves made of the following materials:** Leather gloves

· **Eye protection:**



Tightly sealed goggles

EN-Standard: EN 166

· **Body protection:**



Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid
Colour: Colourless

· **Odour:** Ester-like

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 101 °C (MMA)

· **Flash point:** 22 °C (DIN EN ISO 3680)

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 7

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 6)

| | |
|---|---|
| · Ignition temperature: | 430 °C (MMA) |
| · Self-igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1.7 Vol % (MMA) |
| Upper: | 12.5 Vol % (MMA) |
| · Vapour pressure at 20 °C: | 38.7 hPa (MMA) |
| · Density at 20 °C: | 1.03 g/cm ³ (EN ISO 2811-1) |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | log Pow: 4,29 (2-EHA); (25 °C, OECD 107) log Pow: 1,38 (MMA) |
| · Viscosity: | |
| Dynamic at 20 °C: | 600 mPas (EN ISO 2555) |
| · Solvent content: | |
| Organic solvents: | 0.0 % |
| VOC (EC) | 0.00 % |
| Solids content: | 56.0 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** see Section 10.2
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Exothermic reaction.
Reacts with peroxides and other radical forming substances.
A hazardous polymerization may occur after the exhaustion of the inhibitor.
- **10.4 Conditions to avoid** Avoid heat. Avoid direct sunlight.
- **10.5 Incompatible materials:** Violent reaction with peroxides and other reducing agents.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products used according to specifications.
- **Additional information:**
Emergency procedures will vary depending on individual circumstances. The customer should have a contingency plan to the workplace may be present.

* SECTION 11: Toxicological information

- **11.1 Information on toxicological effects** There were no toxicological findings to the mixture.

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 8

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 7)

· **Acute toxicity**

| · LD/LC50 values relevant for classification: | | |
|--|---------|---|
| 80-62-6 methyl methacrylate | | |
| Oral | LD50 | > 5000 mg/kg (rat) (OECD 401) |
| | NOAEL | 2000 ppm (rat) n drinking water, 6-2000 ppm Findings: No toxic effects |
| Dermal | LC50 | > 5000 mg/kg (rabbit) |
| Inhalative | LC50/4h | 29.8 mg/l (rat) |
| | NOAEL | 25 ppm (rat) 25 - 400 ppm Findings: Damage to mucous membranes in the nose at 400 ppm |
| 25068-38-6 Bisphenol-A-epichlorohydrin | | |
| Oral | LD50 | >5000 mg/kg (rat) |
| Aromatisches Urethanacrylharz | | |
| Oral | LD50 | >2000 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rabbit) |
| 103-11-7 2-ethylhexyl acrylate | | |
| Oral | LD50 | 4435 mg/kg (rat) (BASF-Test) |
| Dermal | LC50 | 7520 mg/kg (hare) |

· **Primary irritant effect:**

· **Skin corrosion/irritation**

Causes skin irritation.

· **Serious eye damage/irritation**

Causes serious eye irritation.

· **Respiratory or skin sensitisation**

May cause an allergic skin reaction.

· **Other information (about experimental toxicology):**

Due to the high vapor pressure is a harmful concentration in the air quickly been reached. At high concentrations can occur narcotic effect.

· **Subacute to chronic toxicity:** not tested

· **Toxicokinetics, metabolism and distribution** The drug is metabolized rapidly (MMA).

· **Repeated dose toxicity** no data available

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)** not tested

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure**

May cause respiratory irritation.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

80-62-6 methyl methacrylate

EC3/16h | 100 mg/l (Pseudomonas putida) (Zellvermehrungshemmtest, Bringmann-Kühn)

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 9

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 8)

| | |
|---|---|
| · Aquatic toxicity: | |
| 80-62-6 methyl methacrylate | |
| EC50/48h | 69 mg/l (daphnia magna) (OECD 202) |
| EC50/72h | > 110 mg/l (Senastrum capricornutum) (OECD 201) |
| ErC50/72h | > 110 mg/l (Pseudokirchneriella subcapitata) (OECD 201) |
| LC50/96h | > 79 mg/l (Rainbow trout) (OECD 203) |
| NOEC | 9.4 mg/l (Danio rerio) (OECD 210) fish early life stage test, 35 days |
| | 37 mg/l (daphnia magna) (OECD 211) 21 days |
| NOEC/72h | > 110 mg/l (Senastrum capricornutum) (OECD 201) |
| 25068-38-6 Bisphenol-A-epichlorohydrin | |
| EC50/48h (static) | 1.7 mg/l (daphnia magna) (OECD 202, Acute Immobilisation Test) |
| EC50/72h (static) | 9.4 mg/l (Alge (Desmodesmus subspicatus)) |
| LC50/96h (static) | 1.5 mg/l (fish) (OECD 203, Acute Toxicity Test) |
| NOEC/21d | 0.3 mg/l (daphnia magna) (OECD 211, Reproduction Test) |
| 103-11-7 2-ethylhexyl acrylate | |
| EC50/48h (static) | 1.3 mg/l (daphnia magna) (OECD 202, Part 1) |
| ErC50/72h (static) | 1.71 mg/l (scenedesmus subspicatus) (OECD 201) The details of the toxic effect relates to the analytically determined concentration. |
| LC50/96h (static) | 1.81 mg/l (Rainbow trout) (OECD 203) |
| NOEC/21d | 0.19 mg/l (daphnia magna) The details of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from products of a similar structure or composition. |
| other (28d) | > 1000 mg/kg (Soil microorganisms) (OECD 217) |

· **12.2 Persistence and degradability** Easily biodegradable

· **Other information:** The product is easily biodegradable.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil**

MMA: A binding to the solid phase of soil, sediment and sewage sludge is not expected. From the water surface the substance is slowly evaporated into the atmosphere. Where the substance into the environment he verleiht preferably in the compartment into which it has emerged.

· **Additional ecological information:**

· **BOD5-value:** 0.14 g/g (MMA)

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

· **vPvB:** Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

· **12.6 Other adverse effects** No further relevant information available.

* SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

Hazardous waste according to Waste Catalogue (EWC). If recycling is not possible, waste must be in compliance with local regulations to be removed.

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 10

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 9)

· **Recommendation**

Uncured product residues are special waste.
Cured product residues are not hazardous waste.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste disposal key:**

The following Waste Codes of the European Waste Catalogue (EWC), are considered a recommendation. The disposal must be coordinated with the local waste disposal company.

Liquid product:

080111 * paint and varnish containing organic solvents or other dangerous substances

080199 waste nec

Cured product residues:

080112 paint and varnish wastes other than those mentioned in 080111

080410 adhesive waste adhesives and sealants other than those mentioned in 080409

· **European waste catalogue** 080111 * (recommended)

· **Uncleaned packaging:**

· **Recommendation:**

This material and its container must be disposed of as hazardous waste.
Disposal must be made according to official regulations.

* SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**

· **ADR**

· **IMDG, IATA**

1263 PAINT, special provision 640H
PAINT

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class**

· **Label**

3 Flammable liquids.

3

· **14.4 Packing group**

· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

· **Danger code (Kemler):**

· **EMS Number:**

Warning: Flammable liquids.

-

F-E,S-E

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Contd. on page 11)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 11

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 10)

· **Transport/Additional information:**

| | |
|-----------------------------------|--|
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · Transport category | 3 |
| · Tunnel restriction code | E |
| · Remarks: | Classification according to viscosity clause (2.2.3.1.4) |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · Remarks: | Classification according to viscosity clause (2.3.2.3) |
| · UN "Model Regulation": | UN 1263 PAINT, SPECIAL PROVISION 640H, 3, III |

* SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations:**
- **Information about limitation of use:**
Employment restrictions under the Maternity Protection Directive (94/33/EC).
Employment restrictions for maternity Directive (92/85/EEC) for expectant and nursing mothers.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

These figures relate to the product as delivered.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Sector of Use

Relevant identified uses of the mixture

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

SU21 Consumer uses: Private households / general public / consumers

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 12)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Page 12

Revision: 17.03.2015

Trade name: RENOLIT ALKORPLUS 81802-001– POLIQUID COMBI-PRIMER

(Contd. of page 11)

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Training hints**

Teaching about hazards and precautions to hand the operating instructions (Technical Rule 555).
Instruction must take place before the start of employment and at least annually thereafter.

· **Department issuing MSDS:** Division product safety

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic vPvB:
very Persistent and very Bioaccumulative Flam. Liq.
2: Flammable liquids, Hazard Category 2
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· **Sources**

- www.gestis.de
- www.echa.eu
- logkow.cisti.nrc.ca

· * **Data compared to the previous version altered.**