



Accessories

Metalsheet	81191
Corners	81092/81093/81094
Detailing membrane	35091002/35096011
Walkway	

Accessories

ALKORFLEX[®] 81191 metalsheet

Galvanised 0.6 mm sheet with an 0.5 mm unreinforced ALKORFLEX[®] membrane laminated to the surface. The reverse face is treated with an anti-corrosion coating:

- UV stabilised
- excellent lamination strength
- can be cut and formed into any required shape using standard metal bending equipment
- excellent mechanical properties

Application:

Specifically designed as an accessory for ALKORFLEX[®] roofing systems to provide high quality upstands and parapets:

- intermediate support on unbonded upstands over 500 mm high
- linear edge restraint
- metal profiles to cover parapets

Type Number	Thickness (NBN A43-201)	Colour	Width	Length	Weight	Quantity per Pallet
81191101	1.1 mm	light grey 71043	1.0 m	2.0 m	5.4 kg/m ²	30 sheets

ALKORFLEX[®] 81092/81093/81094 corners

ALKORFLEX[®] inner (81092) and outer corners (81093) as well as roof light 70° corners (81094) provide a reliable and neat finish to various corner situations:

- unreinforced ALKORFLEX[®]
- colour: light grey

ALKORFLEX[®] detailing membrane

ALKORFLEX[®] 35091002, 1.5 mm unreinforced detailing membrane is supplied in rolls 1.05 m x 20 m and used to waterproof details such as outlets and pipe penetrations.

ALKORFLEX[®] 35096011, 1.2 mm reinforced detailing membrane is supplied in rolls 200 mm x 25 m as a junction strip for waterproofing seams and Alkormetal sections.

ALKORFLEX[®] walkway

ALKORFLEX[®] walkway membrane for delineating maintenance access and emergency routes. Charcoal colour, 1,2 mm thick, reinforced.

November 2002

RENOLIT Cramlington Ltd.

Axis 5,
Rhodes Way
Watford, Herts
WD24 4TN
Great Britain
Tel: +44 (0) 1923/24 95 11
Fax: +44 (0) 1923/22 74 27

