



# Accessories

 Metalsheet
 81191

 Corners
 81092/81093/81094

 Detailing membrane
 35091002/35096011

 Walkway
 Valkway





# Accessories

# ALKORFLEX<sup>®</sup> 81191 metalsheet

Galvanised 0.6 mm sheet with an 0.5 mm unreinforced ALKORFLEX® membrane laminated to the surface. The reverse face is treated with an anti-corrosion coating:

- UV stabilised
- excellent lamination strength
- can be cut and formed into any required shape using standard metal bending equipment
- excellent mechanical properties

#### **Application:**

Specifically designed as an accessory for ALKORFLEX® roofing systems to provide high quality upstands and parapets:

- intermediate support on unbonded upstands over 500 mm high
- linear edge restraint
- metal profiles to cover parapets

Type Number	Thickness (NBN A43-201)	Colour	Width	Length	Weight	Quantity per Pallet
81191101	1.1 mm	light grey 71043	1.0 m	2.0 m	5.4 kg/m <sup>2</sup>	30 sheets

# ALKORFLEX® 81092/81093/81094 corners

ALKORFLEX® inner (81092) and outer corners (81093) as well as roof light 70° corners (81094) provide a reliable and neat finish to various corner situations:

unreinforced ALKORFLEX®

• colour: light grey

# ALKORFLEX® detailing membrane

ALKORFLEX® 35091002, 1.5 mm unreinforced detailing membrane is supplied in rolls 1.05 m x 20 m and used to waterproof details such as outlets and pipe penetrations.

ALKORFLEX® 35096011, 1.2 mm reinforced detailing membrane is supplied in rolls 200 mm x 25 m as a junction strip for waterproofing seams and Alkormetal sections.

# ALKORFLEX<sup>®</sup> walkway

ALKORFLEX® walkway membrane for delineating maintenance access and emergency routes. Charcoal colour, 1,2 mm thick, reinforced.

November 2002



**RENOLIT** Great Brtitain LTD

Axis 5, Rhodes Way Watford, Herts WD24 4TN Great Britain Tel: +44 (0) 1923/24 95 11 Fax: +44 (0) 1923/22 74 27