

DECLARATION OF PERFORMANCE N°

1. Unique identification code of the product-type

2. Intended use

3. Manufacturer

4. Authorised representative

5. System of AVCP

6a. Harmonised standard

Notified Body

6b. European Assessment Document

Notified Body

7. Declared performances

External fire performance (CEN/TS 1187)

Reaction to fire (EN 13501-1)

Watertightness (EN 1928)

Tensile force (EN 12311-2/A)

Elongation (EN 12311-2/A)

Resistance to root penetration (EN 13948)

Resistance to static load (EN 12730/B and C)

Resistance to impact (EN 12691/A)

Resistance to impact (EN 12691/B)

Tear resistance (EN 12310-2)

Joint peel resistance (EN 12316-2)

Joint shear resistance (EN 12317-2)

Artificial ageing (EN 1297)

Foldability at low temperature (EN 495-5)

Dangerous substances

* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) N° 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Oudenaarde

F35276121017

ALKORPLAN F 35276

Plastic sheets for roof waterproofing
Exposed sheets - Mechanically fastened

Renolit Belgium NV

Industriepark De Bruwaan 43

9700 Oudenaarde - Belgium

-

System 2+

EN 13956 : 2012

BCCA N° 0749

-

Froof

E

Pass

MLV >= 1050 N/50 mm

MLV >= 15 %

-

MLV >= 20 kg

MLV >= 600 mm

MLV >= 2000 mm

MLV >= 200 N

MLV >= BOJ or 200 N/50 mm

MLV >= BOJ or 1050 N/50 mm

Grade 0

MLV <= - 25 °C

Conform *

Manufacturer instructions

Dirk Van der Sype
07/02/2019



A handwritten signature in blue ink, appearing to read 'Dirk Van der Sype', written over a horizontal line.

DECLARATION OF PERFORMANCE N°

1. Unique identification code of the product-type

2. Intended use

3. Manufacturer

4. Authorised representative

5. System of AVCP

6a. Harmonised standard

Notified Body

6b. European Assessment Document

Notified Body

7. Declared performances

External fire performance (CEN/TS 1187)

Reaction to fire (EN 13501-1)

Watertightness (EN 1928)

Tensile force (EN 12311-2/A)

Elongation (EN 12311-2/A)

Resistance to root penetration (EN 13948)

Resistance to static load (EN 12730/B and C)

Resistance to impact (EN 12691/A)

Resistance to impact (EN 12691/B)

Tear resistance (EN 12310-2)

Joint peel resistance (EN 12316-2)

Joint shear resistance (EN 12317-2)

Artificial ageing (EN 1297)

Foldability at low temperature (EN 495-5)

Dangerous substances

* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) N° 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Oudenaarde

F35276151017

ALKORPLAN F 35276

Plastic sheets for roof waterproofing
Exposed sheets - Mechanically fastened

Renolit Belgium NV

Industriepark De Bruwaan 43

9700 Oudenaarde - Belgium

-

System 2+

EN 13956 : 2012

BCCA N° 0749

-

Froof

E

Pass

MLV >= 1100 N/50 mm

MLV >= 16 %

-

MLV >= 20 kg

MLV >= 700 mm

MLV >= 2000 mm

MLV >= 225 N

MLV >= BOJ or 225 N/50 mm

MLV >= BOJ or 1100 N/50 mm

Grade 0

MLV <= - 25 °C

Conform *

Manufacturer instructions

Dirk Van der Sype
07/02/2019



A handwritten signature in blue ink, appearing to read 'Dirk Van der Sype', written over a horizontal line.

DECLARATION OF PERFORMANCE N°

1. Unique identification code of the product-type

2. Intended use

3. Manufacturer

4. Authorised representative

5. System of AVCP

6a. Harmonised standard

Notified Body

6b. European Assessment Document

Notified Body

7. Declared performances

External fire performance (CEN/TS 1187)

Reaction to fire (EN 13501-1)

Watertightness (EN 1928)

Tensile force (EN 12311-2/A)

Elongation (EN 12311-2/A)

Resistance to root penetration (EN 13948)

Resistance to static load (EN 12730/B and C)

Resistance to impact (EN 12691/A)

Resistance to impact (EN 12691/B)

Tear resistance (EN 12310-2)

Joint peel resistance (EN 12316-2)

Joint shear resistance (EN 12317-2)

Artificial ageing (EN 1297)

Foldability at low temperature (EN 495-5)

Dangerous substances

* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) N° 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Oudenaarde



F35276181017

ALKORPLAN F 35276

Plastic sheets for roof waterproofing
Exposed sheets - Mechanically fastened

Renolit Belgium NV

Industriepark De Bruwaan 43

9700 Oudenaarde - Belgium

-

System 2+

EN 13956 : 2012

BCCA N° 0749

-

Froof

E

Pass

MLV >= 1125 N/50 mm

MLV >= 16 %

-

MLV >= 20 kg

MLV >= 800 mm

MLV >= 2000 mm

MLV >= 250 N

MLV >= BOJ or 250 N/50 mm

MLV >= BOJ or 1125 N/50 mm

Grade 0

MLV <= - 25 °C

Conform *

Manufacturer instructions

Dirk Van der Sype
07/02/2019

A handwritten signature in blue ink, appearing to read 'Dirk Van der Sype', written over a horizontal line.

DECLARATION OF PERFORMANCE N°

1. Unique identification code of the product-type

2. Intended use

3. Manufacturer

4. Authorised representative

5. System of AVCP

6a. Harmonised standard

Notified Body

6b. European Assessment Document

Notified Body

7. Declared performances

External fire performance (CEN/TS 1187)

Reaction to fire (EN 13501-1)

Watertightness (EN 1928)

Tensile force (EN 12311-2/A)

Elongation (EN 12311-2/A)

Resistance to root penetration (EN 13948)

Resistance to static load (EN 12730/B and C)

Resistance to impact (EN 12691/A)

Resistance to impact (EN 12691/B)

Tear resistance (EN 12310-2)

Joint peel resistance (EN 12316-2)

Joint shear resistance (EN 12317-2)

Artificial ageing (EN 1297)

Foldability at low temperature (EN 495-5)

Dangerous substances

* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) N° 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Oudenaarde



F35276201017

ALKORPLAN F 35276

Plastic sheets for roof waterproofing
Exposed sheets - Mechanically fastened

Renolit Belgium NV

Industriepark De Bruwaan 43

9700 Oudenaarde - Belgium

-

System 2+

EN 13956 : 2012

BCCA N° 0749

-

Froof

E

Pass

MLV >= 1150 N/50 mm

MLV >= 16 %

-

MLV >= 20 kg

MLV >= 1000 mm

MLV >= 2000 mm

MLV >= 275 N

MLV >= BOJ or 275 N/50 mm

MLV >= BOJ or 1150 N/50 mm

Grade 0

MLV <= - 25 °C

Conform *

Manufacturer instructions

Dirk Van der Sype
07/02/2019

A handwritten signature in blue ink, appearing to read 'Dirk Van der Sype', written over a horizontal line.