

## Natural swimming pools.

**RENOLIT** ALKORPLAN






## **ADVANTAGES**

- · Can be installed without wrinkles or folds.
- Makes it easy to line stairs and difficult shapes.
- RENOLIT ALKORPLAN natural swimming pond liner is a 1.5 mm thick polyester reinforced liner that guarantees long term water fun in your garden.
- RENOLIT ALKORPLAN liners are hot air welded which guarantees a homogeneous and perfectly watertight finish.
- Accidental damages can be repaired throughout the entire lifecycle of the membrane in a simple and professional way.
- RENOLIT ALKORPLAN natural swimming pool liner is fish and plant friendly





## RENOLIT ALKORPLAN<sub>00328</sub>

- Tensile strength: 800N/50 mm (according DIN 53455)
- Elongation at break: nominal value 10% (according DIN 53455)
- Tear strength: nominal value 100 N (according DIN 53363)
- Shrinkage: nominal value < 1% (according DIN 53377, 6 h/80°C)
- Cold crack temperature: nominal value -20°C N (according DIN 53361)
- Root resistance: no perforations (according DIN 4062 5.7)

Subject to change without notice.

OLIVE GREEN 67793 BLACK 99040

The black colour makes the water warm up faster.

The information contained in the present commercial literature has been given in good faith and with the intention of providing information. It is based on current knowledge at the time of issue, and may be subject to change without notice. Nothing contained herein may induce the application of our products without observing existing patents, certificates, legal regulations, national or local rules, technical approvals or technical specifications or the rules and practices of good workmanship for this profession. The purchaser should verify whether import, advertising, packaging, labelling, composition, possession, ownership and the use of our products or the commercialisation of them are subject to specific territorial rules. He is also the sole person responsible for informing and advising the final end user. When faced with specific cases or application details not dealt with in the present guidelines, it is important to contact our technical services, who will give advice, based on the information at hand and within the limitations of their field of expertise. Our technical services cannot be held responsible for the conception of, nor the execution of the works. In the case of negligence of rules, regulations and duties on the part of the purchaser we will disclaim all responsibility. The colours respect the UV resistance required by EOTA, but are still subject to the natural change over time. Are excluded from the guarantee: aesthetic considerations in case of partial repair of deficient membrane covered by the quarantee.

## WWW.RENOLIT.COM/ROOFING





RENOLIT roofing products and systems have a standard guarantee of 10 years, and are installed by approved contractors and installers who are trained and assessed by RENOLIT. The RENOLIT division responsible for the roofing activity has been approved to EN ISO 9001:2008.

